

PRODUCT SPECS:

FIBER TYPE:	TEXTURIZED POLETHYLENE
PILE HIEGHT:	1/2"
FIBER TOLERANCE:	HEAVEY FOOT TRAFIC
FIBER COLOR:	OLIVE GREEN / FIELD GREEN
THATCH COLOR:	N/A
TUFT GAUGE:	3/16"
STICH RATE:	32 PER 3 7/8"
FACE WEIGHT:	52 OZ / SQ YD
BACKING:	POLYURETHANE
TOTAL WEIGHT:	80 OZ / PER SQ YD
ROLL SIZE:	13' X 82'
ROLL WEIGHT:	592 IBS
DRAINAGE WEIGHT:	N/A
SEEMING DIFFICULTY:	HIGH



INSTALLATION STEPS:

- 1. EXCAVATE MINIMUM OF 6" SOD AND SOIL
- 2. BACKFILL WITH A MINIMUM 2' OF DRAIN ROCK AND COMPACT TO 90%
- 3. INSTALL GEOTEXTILE WEED BARRIEIR
- 4. BACKFILL WITH 4" OF CLASS II ROAD BASE, QUARRIED 19mm MINUS AND COMPACT TO 90%
- 5. ADD LAYERS OF ROCK DUST FOR DESIRED SURFACE SLOPES AND CONTUREING & COMPACT TO 90%
- 6. CUT PUTTING GREEN TO DESIGN SPEC AND IN-STALL.THE GRASS MUST BE INSTALLED AND SEEMED WITH THE ADJACENT PIECES RUNNING IN THE SAME DIRECTION; SEEMS SHOULD BE GLUED WITH NORDOT #34N2 SEEMING GLUE AND SEEMING CLOTH; NOT ADHESIVE TAPE
- 7. INSTALL FRINGE TO DESIGN SPEC
- 8. INFILL PUTTING SURFACE IN MULTIPLE LAYERS UNTIL YOU ACHIEVE DESIRED BALL SPEED
- 9. INFILL FRINGE & LANDSCAPE SURROUNDING AREA
- 10. ONCE GRASS IS INSTALLED TO SPEC, SEEMED, AND INFILLED, SOAK THE ENTIRE AREA WITH WATER



